



art. 8034 LITTLE-LORD/AR

Mod	AR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	45° asymmetric beam matt satin aluminium reflector
Power supply	220-240V 50/60Hz	Flicker	Low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	45°		

CODING

Art.	+	Mod.	+	°K	+		+	W-tot.	+	Opt.		
8034		AR		3	=3000°K-CRI80		6	=6500°K-CRI80	080	130	EL	=on/off
				4	=4000°K-CRI80				100	150	LD	=dali
				5	=5000°K-CRI80				120		LM	=1-10V
											VI	=vetro infrangibile
											VA	=vetro acidato
											LG	=mezzanotte virtuale
											E1	=em. 1h

ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.085	Acc.086	Acc.087	

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
80	2	150W JM/SAP	13527	10222	128	295	100	355	4,9
100	2	150W JM/SAP	17172	12978	130	295	100	355	4,9
120	2	250W JM/SAP	18684	14120	118	295	100	355	4,9
130	2	250W JM/SAP	20361	15387	118	295	100	355	4,9
150	2	250W JM/SAP	22315	16864	112	295	145	355	5,7

The luminous flux and the total power absorbed by the system have a tolerance of $\pm 10\%$ with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90 = -13,73% lm

