



art. 8029 LORDINO/PR

Mod	PR	Installation	Indoor and outdoor floodlight
Material	Die cast aluminium body, painted with polyester coated anticorrosion powder anthracite color, tempered transparent glass mm 5 thickness, silicon gasket	Insulation class	Class I
Protection index	IP66	Impact degree	IK08
Ambient temperature (Ta)	-25 / +45 °C	Optics	110° wide beam matt satin aluminium reflector
Power supply	220-240V 50/60Hz	Flicker	Low flicker (less than 7%)
Trademarks and certifications	CE / UNI EN 60598-1:2015	Warranty	7 YEARS
Luminous flux maintenance	L80-B20 (50.000h) - L80-B50 (75.000h)	Photobiological safety class	IEC 62471: Exempt group
Beam angle	110°		

CODING

Art.	+	Mod.	+	°K	+	W-tot.	+	Opt.		
8029		PR		30	=3000°K-CRI80	65	=6500°K-CRI80	20	50	EL =on/off
				40	=4000°K-CRI80	93	=3000°K-CRI90	30	68	LD =dali
				50	=5000°K-CRI80	94	= 4000°K-CRI90	40		LM =1-10V
										VI =vetro infrangibile
										VA =vetro acidato

ACCESSORIES

Acc.068	Acc.069	Acc.070	Acc.071
Acc.082	Acc.083	Acc.084	

PERFORMANCE

W tot.	N°led	REPLACE	LUMEN LED	LUMEN OUTPUT	Lm/W	A(mm)	B(mm)	C(mm)	Kg
20	1	300W ALO	3214	2490	125	180	65	330	2
30	1	70W JM	4518	3500	117	180	65	330	2
40	1	70W SAP	6763	5238	131	180	65	330	2
50	1	100W JM/SAP	7102	5485	110	180	65	330	2
68	1	150W JM	9845	7626	112	180	65	330	2

The luminous flux and the total power absorbed by the system have a tolerance of $\pm 10\%$ with respect to the indicated values.

- 3000K - CRI80 = -4,5% lm
- 3000K - CRI90 = -19,9% lm
- 4000K - CRI80 = standard
- 4000K - CRI90= -13,73% lm

