

LED Driver 24V 150W IP67

EI-nr: 6651162

EGENSKAPER

LED Driver for konstant spenning (24V) for bruk til blant annet

LED Stripes. For utendørs bruk, IP67. Aluminium. Leveres med ledning med løs ende på primær- og sekundærside



HOVEDFUNKSJONER

- Høy effektivitet (Opp til 93%)
- Active Power Factor Correction
- 24V DC
- Constant Voltage Output
- 100~277VAC, 50/60Hz
- Vanntett IP67

TEKNISKE DATA

- Driftsspenning: 100~277VAC, 50/60Hz
- Input Current: 2A @ 100VAC, 0.8 @ 220VAC
- Utgangsspenning: 24VDC±5% (Maks.)
- Utgangstrøm: 0-6.25A
- Beskyttelse: Kortslutning-, overbelastning- og overspenningsbeskyttelse
- Effekt 0-150W
- Vekt: 1000g
- Beskyttelsesklasse: IP67
- Levetid: 77 000h ved +60° @220Vac, 80% last
- Godkjenninger: CE, EN 55015, EN 61000-3-2, EN 61000-3-3,
- FCC Part 15 ANSI C63.4: 2009 Class B, EN 61000-4-2
- EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11, EN 61547

TILKOBLING

- Kabel størrelse: 7,8mm²
- Avmantlingslengde: 15mm

The technical drawing shows two views of the cable assembly. The top view is a side elevation showing the overall length and connector details. Dimensions include 207.00, 230.00, 192.00, 6.00, 502.3, 541, 300±15, 183.20, and 300±15. Part numbers 502.3 and 541 are indicated near the connectors. The bottom view is a cross-section or end view showing the cable's profile with dimensions 20.00, 10.00, 10.00, and 10.00. A legend indicates 'Red' and 'Black' wire colors.

El-nr	Type	Spenning ut (V)	Effekt (W)	Utgangsstrøm(A)	Ta°C	Tc°C	Power factor
66 511 62	LED Driver 150W 24V IP67	24V	150W maks	0-6.25A	-35 +70°C	80°C	0.99