

## uSee Interface (8800)

uSee is a web-based lighting system management interface that allows end users to monitor their energy usage and adjust scene levels via most web access devices, including iPad, PC, tablets and iPhone.

The uSee Interface puts the management of a lighting system in the hand of end-users, without any need for Designer programming software knowledge.

The contemporary and intuitive design allows end users to call up real-time energy usage reports in a few easy steps.

uSee works by automatically scanning your lighting system's Designer programme settings and interpreting them into plain language so that the people who use the system day-to-day can make adjustments to their scene setting levels and rename label fields to suite their need.

## Key Features

- Connect wirelessly or via wired Ethernet
- Control your lighting network from iPad, PC, smartphone: most devices that have web browsing capabilities
- Easy to use, enabling scene level editing and recall without any programming experience.
- Monitor your energy usage and make money-saving adjustments.
- Simple fine-tuning of access and user settings




freedom in lighting




### Access via web browser




## Group Settings




## Scene Recall



## Emergency Test Schedule



## Energy Monitoring



## Technical Data

### Power

Mains supply: 88 VAC – 264 VAC  
47 Hz – 63 Hz

Power consumption: 14 W

Protection: Max. 6 A MCB

Supply current: 0.55 A / 230 V

DALI consumption: 2 mA

### Cable requirements

Gland cable range:  $\varnothing$  5 mm – 10 mm

### Mechanical data

Dimensions: 279 mm × 234 mm × 59 mm

Installation: Wall mounted. Leave sufficient clearance (at least 10 cm) to allow cables to be connected.

Weight: 2.9 kg

IP code: IP20

### Operating and storage conditions

Ambient temperature: 0 °C to +40 °C

Relative humidity: Max. 90 %, non-condensing

Storage temperature: -10 °C to +70 °C

### Conformity and standards

Emission: EN 55022

Immunity: EN 61000

Safety: EN 60950

Isolation: 3 kV

Environment: Complies with WEEE and RoHS directives

**Class A product:** This is a Class A product. In a domestic environment, this product may cause radio interference. In this case, the user may be required to take adequate measures.

## Dimensions

