

LED DRIVER DC MAXI JOLLY HC MD

El-nr: 127550

LED DRIVER DC MAXI JOLLY HC MD

Multipower driver leveres med dip-bryter for valget av utgangsstrømmen. Doble rekkeklemmer for å sløye andre drivere (maks. 5 A). (3)




Funksjoner:

- IP20 uavhengig driver, for innendørs bruk.
- Klasse I-beskyttelse mot elektrisk støt for direkte eller indirekte ta kontakt med.
- Den kan brukes til belysningsutstyr i beskyttelsesklasse I.
- Active Power Factor Corrector.
- Nåværende regulering $\pm 5\%$ inkludert temperaturvariasjoner.
- Inngangs- og utgangsklemmer på samme side (ledertverrsnitt opptil 1,5 - 2,5 mm² / AWG15 - AWG13).
- Klemskruer på primære og sekundære kretser for kabler med diameter: min. 3 mm - maks. 8 mm.
- Termisk beskyttelse = C.5.a.


Beskyttelse:

- mot overoppheting og kortslutning;
- mot nettspenningsspiques;
- mot overbelastning.

Målskisse



Koblingsskjema



Wiring diagram for a 100W LED strip light. The diagram shows the connections between the power supply (PSU) and the LED strip. The PSU has terminals for +V, -V, and GND. The LED strip has terminals for +V, -V, and GND. The diagram shows the connections between the PSU and the LED strip.



Wiring diagram for a 100W LED strip light. The diagram shows the connections between the power supply (PSU) and the LED strip. The PSU has terminals for +V, -V, and GND. The LED strip has terminals for +V, -V, and GND. The diagram shows the connections between the PSU and the LED strip.